# ● CHANNEL VISION<sup>™</sup>

## 1.3 MP Mini IP Dome Camera 6532

Channel Vision's 6532 1.3 Megapixel Mini IP Dome Camera offers superior image quality with a 1.3 megapixel CMOS sensor and has the ability to deliver images up to 720p (1280x800 pixels) at 30 frames per second. The 6532's advanced features like Digital Wide Dynamic Range, Triple Streaming, Power Over Ethernet, Digital Noise Reduction and its IP66 Rated design makes this the perfect camera for all conditions. View and control the 6532 anywhere in the world with an internet browser or Channel Vision's iOS and Android applications. Power supply 5015PS Not Included.

#### Features

Full HD 720P Resolution at 30 frames per second

Micro SD card recording slot inside the camera

4.2mm Fixed Focal Length Lens

Multi-Stream H.264, MJPEG and MPEG4

Wide Dynamic Range for superior image quality in low lighting

Mini IP66 Rated Vandal proof design

Power Over Ethernet or 12vDC Power Supply

Monitor on iPhone/Android with Channel Vision's Application

#### HARDWARE

CPU: ARM 9 ,32 bit RISC RAM: 128MB Flash: 16MB Image Sensor: 1 / 4" 1.3 Mega-Pixel CMOS sensor Sensitivity: 1.0 Lux @30fps Shutter Time: 1 / 5 ~ 1 / 10,000 sec Lens Type: 4.2mm@F1.6 I/0: DI/D0 Power Over Ethernet: Yes, 48V Power consumption, Max: 2.8W Power: DC12V Power consumption, Max: 2.04W, 170mA IP66 Water Proof Rating: Yes Operating Temperature: -10°C ~ 45°C Dimensions: 3.15" DIA x 2.64" H Weight: 11.99 ounces

### NETWORK

Ethernet: 10 / 100 Base-T

**Network Protocol:** HTTP, HTTPS, SNMP, QoS/DSCP, Access list, IEEE 802.1X, RTSP, TCP/IP, UDP, SMTP, FTP, PPPoE, DHCP, DDNS, NTP, UPnP, 3GPP, SAMBA, Bonjour

### **REMOTE VIEWING**

**OS:** Windows 2000, XP, Vista, 7 **Browser:** Microsoft IE 6.0 or above Safari, Chrome





#### SYSTEM

Video Resolution: 1280x800@30fps.1280x720@30fps. 640x480@30fps. 320x240@30fps, 176x144@30fps Video Adjust: Brightness, Contrast, Hue, Saturation, Sharpness, AGC. Shutter Speed adjustable, Sense-Up, D-WDR, Flip, Mirror, Noise reduction, DNR Triple Streaming: Yes Image Snapshot: Yes Full Screen Monitoring: Yes **Privacy Mask:** Yes, 3 different areas Compression Format: H.264/ M-JPEG/ MPEG4 Video Bitrates Adjust: CBR, VBR Motion Detection: Yes, 3 different areas Triggered Action: Mail, FTP, Save to SD card, SAMBA Security: Password protection, IP address filtering, HTTPS encrypted data transmission, 802.1X port-based authentication for network protection. QoS/DSCP Firmware Upgrade: HTTP mode, can be upgraded remotely Simultaneous Connection: Up to 10

### MICRO SD CARD MANAGEMENT

Recording Trigger: Motion Detection, IP check, Network break down, Schedule Video Format: AVI, JPEG Video Playback: Yes Delete Files: Yes

\*Specifications subject to change. iOS and Android are registered trademarks of their respective companies.















www.channelvision.com Toll Free: 800.840.0288 Local: 714.424.6500 234 Fischer Ave. Costa Mesa, CA 92626 USA

Surveillance Systems

Structured Wiring

ercom & Telephone IR Remot Entry Systems Distril

IR Remote Control A Distribution

Audio & Video Distribution